COMMERCIAL MODELS:

DIXIE CHOPPER



2448KW 24hp, 48" Deck

2454KW 24hp, 54" Deck

2460KW 24hp, 60" Deck

The **BlackHawk** is built to redefine your mowing experience with superior value, advanced operator controls, commercial grade components, and unmatched performance.

- **Proven Power -** Equipped with 24 horsepower Kawasaki* engines for years of trusted reliability and performance.
- Robust Deck Offered in three cutting widths, the BlackHawk deck features a deep 7 gauge shell and abrasion resistance baffles to outlast the competition in extreme conditions.
- **Smoothest Steering** The Parker* transmissions off er super smooth steering up to 14 kilometres per hour in a compact, quiet, and efficient drivetrain.
- **Total Comfort** The padded and over-sized bolstered seat hugs your torso for ultimate comfort.
- Peer' Turf Xtreme™ Spindles Maintenance free and constructed of high-strength ductile iron.
- **R.O.P.S.** Roll-over protection system comes standard to keep operators safe.
- **Ready to Accessorize** The BlackHawk is ready to add a suite of accessories including Springer Forks, suspension seat, light kit, striping kit, and more.



Kawasaki Engines - Reliable power to tackle the toughest jobs



Parker* **HTE -** Smooth steering and 1,000 hour oil change intervals



48", 54", and 60" Decks - Deep 7 gauge shell to tackle deep grass



BlackHawk 2454KW shown

Hitch Receiver - Class 1 hitch for easier mounting of accessories



PEER' Spindles - Maintenance free with Contamination Exclusion Technology



*Unlimited hour limited warranty, see dealer for complete warranty details





	48" Deck	54" Deck	60" Deck
Model	2448KW	2454KW	2460KW
Engine			
Manufacturer	Kawasaki* FT		
Horsepower	24		
Displacement	726cc		
Air-cleaner	2 stage		
Cooling	Air-cooled Air-cooled		
Starter	Electric		
Engine warranty	3-Year		

Drive System			
Dual hydrostatic	Parker® HTE		
Ground speed	14 km/h		
Parking brake	Integrated in transaxle		

Mower Deck					
Deck size	48"	54"	60"		
Acres/hour*	3.4	3.9	4.3		
Cutting height	1" - 5"				
OCDC (operator controlled discharge chute)	Optional accessory (foot-operated)				
Deck height adjustments	Manual lift, 1/4" increments				
Electric lift	Optional				
Deck engagement	Ogura* 150 ft-lbs				
Construction	7 ga formed & welded, Abrasion Resistance Baffles				
Blades	(3) -2.5" x 17"	(3) - 2.5" x 19"	(3) - 2.5" x 20.5"		
Blade tip speed (approximate)	18,500 fpm				
Spindles	1.25" effective diameter machined shaft				
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)				
Anti-scalp rollers	4				
Pulleys	7 ga steel deep groove Vented split 3/8"steel dee		Vented split 3/8"steel deep groove		

General			
Battery	12 Volt, 350cca		
Digital Display	Tachometer, hour meter, fuel gauge		
Fuel capacity	25.5 Litres		
Rear tires	23 x 10.5-12 GrassMaster		
Front tires	13 × 6.5-6		
Frame	Welded C-channel, 7 ga formed		
Floor-pan	Removable, steel		
Seat	High-back adjustable padded seat w/ armrests		
Springer Forks	Optional accessory		

Dimensions				
Overall height (rollbar down)	50"			
Overall height (rollbar up)	71"			
Overall width (chute down)	63.6"	69.6"	76"	
Overall width (chute up)	49.2"	55.4"	61.9"	
Overall length (rollbar down)	85.8"			
Overall length (rollbar up)	81.3"			
Weight	500 kg	505 kg	508 kg	

