

FALCON HPX



COMMERCIAL

MODELS:

2460KW 24hp, 60" Deck



COMMERCIAL CUTTER OR WEEKEND WARRIOR

The **Falcon HPX** is the new standard in entry-level commercial mowing with high-quality features, robust durability, and operator comfort and convenience.

- **Proven Power** – Equipped with 24 horsepower Kawasaki® FT engines for years of trusted reliability and performance.
- **Deep Deck** – The Falcon HPX deck features a deep 10 gauge shell to tackle taller grass with ease.
- **Commercial Drive System** – Hydro-Gear ZT-3100 transaxles offer steel-cut gears, charge pumps, and shock valves for extended drivetrain performance.
- **Total Comfort** – The padded and over-sized bolstered seat hugs your torso for ultimate comfort.
- **Peer® Turf Xtreme™ Spindles** – Maintenance free and constructed of high-strength ductile iron.
- **R.O.P.S.** – Roll-over protection system comes standard to keep operators safe.
- **Charge and Mow** – Keep your mobile device and accessories charged with a USB charging port.
- **Ready to Accessorize** – The Falcon HPX is ready to add a suite of accessories including Springer Forks, suspension seat, OCDC, mulch kit, light kit, striping kit, and more.

Falcon HPX 2460KW shown



Kawasaki® Engines – Reliable power to tackle the toughest jobs



More Traction – Large 22" rear tires with semi-aggressive tread pattern



Hydro-Gear® ZT-3100 – Commercial duty drivetrain with serviceable filters



PEER® Spindles – Maintenance free with Contamination Exclusion Technology



Deep Deck – Deep deck shell to tackle more volume

3 YEAR
BUMPER-TO-BUMPER
WARRANTY*

*Unlimited hour limited warranty, see dealer for complete warranty details



FALCON HPX



60" Deck

Model	2460KW
Engine	
Manufacturer	Kawasaki* FT
Horsepower	24
Displacement	726cc
Air-cleaner	2 stage
Cooling	Air-cooled
Starter	Electric
Engine warranty	3-Year

Drive System	
Dual hydrostatic	Hydro-Gear® ZT-3100
Ground speed	12.5 km/h
Parking brake	Integrated in transaxle

Mower Deck	
Deck size	60"
Acres/hour*	3.9
Cutting height	1.5" - 5"
OCDL (operator controlled discharge chute)	Optional accessory (hand-operated)
Deck height adjustments	Manual lift, 1/2" increments
Deck engagement	Warner® 150 ft-lbs
Construction	10 ga formed & welded
Blades	(3) - 2.5" x 20.5"
Blade tip speed (approximate)	18,500 fpm
Spindles	1.25" effective diameter machined shaft
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)
Anti-scalp rollers	3
Pulleys	Vented split 3/8" steel deep groove

General	
Battery	12 Volt, 300cca
Digital Display	hour meter, tachometer
Fuel capacity	20.5 Litres
Rear tires	22x11-10 - 350 Mag
Front tires	13 x 6.5-6
Frame	Welded 1" x 2", 2" x 2" tube, 11 ga formed
Floor-pan	Removable, steel
Seat	High-back adjustable padded seat w/ armrests
Springer Forks	Optional accessory

Dimensions	
Overall height (rollbar down)	51.5"
Overall height (rollbar up)	71.1"
Overall width (chute down)	76.2"
Overall width (chute up)	60"
Overall length (rollbar down)	78.5"
Overall length (rollbar up)	74.1"
Weight	403 kg