

WHERE COMMERCIAL MEETS COMFORTABLE.

The **BlackHawk HP** provides the superior mowing experience with advanced operator controls, commercial grade components, and best-in-class performance and comfort.

- **Total Comfort** Full suspension seat with padded design provides lateral stability and comfort.
- **Proven Power** Equipped with the industry preferred Kawasaki* FX engine for reliability and performance year after year.
- **Smoothest Steering** The Parker* transmissions off er super smooth steering up to 16 kilometres per hour in a compact, guiet, and efficient drivetrain.
- **Robust Deck** Offered in three cutting widths (48", 54", and 60"), the BlackHawk HP deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- Peer' Turf Xtreme™ Spindles Maintenance free and constructed of high-strength ductile iron.
- **Ready to Accessorize** The BlackHawk HP is ready to add a suite of accessories including Springer Forks, electric deck lift, light kit, striping kit, and more.



Suspension Seat - Full suspension for ultimate comfort all day long



Parker HTJ - Smooth steering and 1,000 hour oil change intervals



48", 54", 60" Decks - Deep 7 gauge shell to tackle tough grass with ease



Kawasaki* **Engines -** Reliable power to tackle the toughest jobs



PEER' Spindles - Maintenance free with Contamination Exclusion Technology



*Unlimited hour limited warranty, see dealer for complete warranty details





	48" Deck	54" Deck	60" Deck	
Model	2448KW	2454KW	2460KW	
Engine				
Manufacturer	Kawasaki* FX			
Horsepower	23.5			
Displacement	726cc			
Air-cleaner	4 stage			
Cooling	Air-cooled Air-cooled			
Starter	Electric			
Engine warranty	3-Year			

Drive System			
Dual hydrostatic	Parker* HTJ		
Ground speed	16 km/h		
Parking brake	Integrated in transaxle		

Mower Deck					
Deck size	48"	54"	60"		
Acres/hour*	3.8	4.3	4.8		
Cutting height	1" - 5"				
OCDC (operator controlled discharge chute)	Optional accessory (foot-operated)				
Deck height adjustments	Manual lift, 1/4" increments				
Electric lift	Optional				
Deck engagement	Ogura [®] 150 ft-lb				
Construction	7 ga formed & welded, Abrasion Resistance Baffles				
Blades	(3) - 2.5" x 17"	(3) - 2.5" x 19"	(3) - 2.5" x 20.5"		
Blade tip speed (approximate)	18,500 fpm				
Spindles	1.25" effective diameter machined shaft				
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)				
Anti-scalp rollers	4				
Pulleys	7 ga vented split steel deep groove				

General				
Battery	12 Volt, 350cca			
Digital Display	Tachometer, hour meter, fuel gauge			
Fuel capacity	25.5 Litres			
Rear tires	23 x 10.5-12 GrassMaster			
Front tires	13 x 6.5-6			
Frame	Welded C-channel, 7 ga formed			
Floor-pan	Removable, steel			
Seat	Full suspension, adjustable seat w/ armrests			
Springer Forks	Optional accessory			

Dimensions					
Overall height (rollbar down)	50"				
Overall height (rollbar up)	71"				
Overall width (chute down)	63.6"	69.6"	76"		
Overall width (chute up)	49.2"	55.4"	61.9"		
Overall length (rollbar down)	85.8"				
Overall length (rollbar up)	81.3"				
Weight	509 kg	513 kg	517 kg		

