

# CLASSIC™

## INDUSTRIAL

### MODELS:

3560KW 35hp, 60" Deck

3572KW 35hp, 72" Deck



Classic 3560KW shown

## A TRUE CLASSIC AMERICAN WORKHORSE.

The **Classic** is the perfect definition of a workhorse mower with the combination of commercial quality and industrial features.

- **Power and More Power** - Equipped with the industry preferred Kawasaki® FX engine with 35 horsepower for trusted performance and reliability.
- **Lifetime Warranty Frame** - The strongest frame in the industry with a 1" x 2" steel-tube chassis guaranteed not to break.
- **T-Gear Box** - Eliminates side-load on pumps and backed with a 5-year or 3,000 hour warranty.
- **Complete Discharge Control** - An operator controlled discharge chute (OCDC) allows you to switch from normal discharge to closing the chute on the fly, saving you time on clean-up.
- **Tried and True Decks** - Offered in two productive deck widths (60" and 72") the Elite X Deck has been the staple piece to Dixie Chopper's reputation of cleanly cutting all types of grass.
- **Comfort Ride** - Our suspension seat comes standard on every Classic model to provide a smooth ride in the roughest terrain.



**Suspension Seat** - Full suspension for ultimate comfort all day long



**More Muscle** - Engine with 35hp and Turbinator Pre-Cleaner



**Pumps & Wheel Motors** - Stronger transmissions for extended system life



**Spindle Package** - Maintenance-free spindles and cooling fans come standard



**60" and 72" Elite X Deck** - Gives a quality cut in all types of grass

**3 YEAR  
BUMPER-TO-BUMPER  
WARRANTY\***

\*Unlimited hour limited warranty, see dealer for complete warranty details



# CLASSIC™



	60" Deck		72" Deck	
Model	3560KW		3572KW	
<b>Engine</b>				
Manufacturer	Kawasaki® FX		Kawasaki® FX	
Horsepower	35		35	
Displacement	999cc		999cc	
Air-cleaner	4 stage & Turbinator® Pre-Cleaner			
Cooling	Air-cooled			
Starter	Electric			
Engine warranty	3-Year			

<b>Drive System</b>				
Pumps	Hydro-Gear® 16cc			
Wheel motors	Parker® DG280			
Ground speed	19 km/h			
Parking brake	Automotive Style			

<b>Mower Deck</b>				
Deck size	60"		72"	
Acres/hour*	5.8		7	
Cutting height	1.25" - 5"			
O CDC (operator controlled discharge chute)	Standard			
Deck height adjustments	Manual lift, 1/4" increments			
Electric lift	Optional			
Deck engagement	Ogura® 250 ft-lbs			
Construction	10 ga formed & welded		7 ga formed & welded	
Top plate	7 ga bolted (not welded)			
Blades	3 - 20.5" x 2.5"		3 - 24" x 2.5"	
Blade tip speed (approximate)	18,000 fpm			
Spindles	1.25" effective diameter machined shaft			
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)			
Spindle cooling fans	Standard (3)			
Anti-scalp rollers	4		5	
Pulleys	Vented split 3/16" steel deep groove			

<b>General</b>				
Battery	12 Volt, 350cca			
Digital display	Tachometer, hour meter, voltmeter, service alerts			
Fuel capacity	37.5 Litres		45 Litres	
Rear tires	25 x 12-12 GrassMaster			
Front tires	15 x 6-8 (run-flat)			
Frame	Welded 1" x 2" tube, 7 ga formed			
Floor-pan	Removable, steel			
Seat	Full suspension, adjustable seat w/ armrests			
Springer Forks	Optional			

<b>Dimensions</b>				
Overall height	53"			
Overall height (rollbar up)	78"			
Overall width	65.5"		76"	
Overall length	78"		80"	
Overall length (rollbar down)	81"		83"	
Weight	557 kg		646 kg	