

EAGLE HP™

COMMERCIAL

MODELS:

3560KW 35hp, 60" Deck

3572KW 35hp, 72" Deck



Eagle HP 3560KW shown

THE ULTIMATE MOWING EXPERIENCE.

The new **Eagle HP** provides the ultimate mowing experience with unmatched combination of speed, power, performance, and comfort.

- **Fast Ground Speed** - Hydro-Gear® ZT-5400 gives operators speeds up to 22.5 km/h for faster ground transportation and increased productivity.
- **Pure Power** - Equipped with the industry preferred Kawasaki® FX engine with 35 horsepower for trusted performance and reliability.
- **Ultimate Comfort** - Springer Forks come standard along with a high-back seat with padded armrests, recline, lumbar, and isolated platform.
- **Robust Deck** - Offered in two cutting widths (60" and 72"), the Eagle HP deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Wide Stance** - Extra-wide frame offers enhanced operator comfort and improved stability when mowing hillsides.
- **Run-Flat Tires** - Flat tires are a problem of the past with run-flat tires standard on the Eagle HP.



Hydro-Gear ZT-5400 - Speeds up to 22.5 km/h for increased productivity



More Muscle - Engine with 35hp and Turbinator Pre-Cleaner



Suspension Seat - High back, padded armrests, and isolated platform



Springer Forks - Absorb bumps to provide smoother ride for operator



60" and 72" Decks - Deep 7 gauge shell to tackle deep grass with ease

**3 YEAR
BUMPER-TO-BUMPER
WARRANTY***

*Unlimited hour limited warranty, see dealer for complete warranty details



EAGLE HP™



	60" Deck		72" Deck	
Model	3560KW		3572KW	
Engine				
Manufacturer	Kawasaki® FX		Kawasaki® FX	
Horsepower	35		35	
Displacement	999cc		999cc	
Air-cleaner	4 stage & Turbinator® Pre-Cleaner			
Cooling	Air-cooled			
Starter	Electric			
Engine warranty	3-Year			

Drive System				
Dual hydrostatic	Hydro-Gear® ZT-5400			
Ground speed	22.5 km/h			
Parking brake	Integrated in transaxle			

Mower Deck				
Deck size	60"		72"	
Acres/hour	6.7		8.1	
Cutting height	1" - 5"			
OCD (operator controlled discharge chute)	Optional accessory (foot-operated)			
Deck height adjustments	Manual lift, 1/4" increments			
Electric lift	Optional			
Deck engagement	Warner® 250 ft-lbs			
Construction	7 ga formed & welded, Abrasion Resistance Baffles			
Blades	(3) - 2.5" x 20.5"		(3) - 2.5" 24.5"	
Blade tip speed (approximate)	18,500 fpm			
Spindles	1.25" effective diameter machined shaft			
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)			
Anti-scalp rollers	4			
Pulleys	Vented split 3/8" steel deep groove			

General				
Battery	12 Volt, 350cca			
Digital Display	Hour meter, fuel gauge			
Fuel capacity	37.5 Litres			
Rear tires	25 x 12-12 GrassMaster			
Front tires	15 x 6-8 (run-flat)			
Frame	Welded C-channel, 7 ga formed			
Floor-pan	Removable, steel			
Seat	High-back, full suspension, lumbar, recline, padded armrests, and isolated platform			
Springer Forks	Standard			

Dimensions				
Overall height (rollbar down)	55.25"			
Overall height (rollbar up)	78.5"			
Overall width (chute down)	77"		89.6"	
Overall width (chute up)	67"		79.6"	
Overall length (rollbar down)	88.6"		90.5"	
Overall length (rollbar up)	88.5"		90.4"	
Weight	670 kg		692 kg	